



RO WARRANTY

Discount Soft Water REVERSE OSMOSIS LIMITED WARRANTY: The Discount Soft Water REVERSE OSMOSIS system is warrantied by Discount Soft Water to be free from defects in materials and workmanship under normal use within the operating parameters listed below for a period of 5 years from the date of installation. Discount Soft Water will provide labor under said warranty at no charge for 1 years from the date of installation. Discount Soft Water under this limited warranty shall be limited, at its option, to replace or repair of any system(s) covered by this Limited Warranty. No warranty is made with respect to defects not reported to Discount Soft Water within the warranty period and/or defects or damages due to neglect, misuse, alterations, accident, misapplication, physical damage, or damage caused by fire, acts of God, freezing or hot water or similar causes. For outdoor installations where the system(s) are not under cover, a weather cover must be utilized for the warranty to be valid.

Discount Soft Water will provide this limited warranty under the following conditions:

- All installation(s), services, maintenance, repairs and parts required are provided by Discount Soft Water, United Waterworks, United Water Softeners or an authorized Discount Soft Water dealer
- Required maintenance is scheduled by customer and performed as outlined herein
- All operational variables are within parameters as outlined herein

DISCOUNT SOFT WATER GIVES THIS WARRANTY TO ORIGINAL PURCHASER ONLY AND THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND HEREBY EXPRESSLY DISCLAIMS ALL OTHER SUCH WARRANTIES. DISCOUNT SOFT WATER LIABILITY HERE UNDER SHALL NOT EXCEED THE COST OF THE PRODUCT. UNDER NO CIRCUMSTANCES WILL DISCOUNT SOFT WATER BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES OR FOR ANY OTHER LOSS, DAMAGE OR EXPENSE OF ANY KIND, INCLUDING LOSS OF PROFITS, ARISING IN CONNECTION WITH THE INSTALLATION OR USE OR INABILITY TO USE THE WATER TREATMENT SYSTEM(S) OR SUPPLY LINE THE WATER TREATMENT SYSTEM(S) IS INCORPORATED INTO.

CONDITIONS FOR OPERATION:

OPERATING PARAMETERS

System Pressure 40psi – 80psi
 Temperature 4 C – 38 C
 PH Range 6.0 – 11.0
 Maximum Feed TDS 970ppm
 Maximum Turbidity 0.9 Ntu

CHEMICAL PARAMETERS

Maximum Hardness 350mg/L
 Maximum Iron 0.1mg/L
 Maximum Manganese 0.05mg/L
 Maximum Hydrogen Sulphide 0.00mg/L
 Maximum Chlorine 2.0mg/L

*Services required:

1 YEAR	TECH RECOMMENDED	2 YEARS
PREFILTER #1	MEMBRANE - TFC	POST FILTER
PREFILTER #2		

**Service records will need to be provided for warranty claims.